

ITEM		UNIT	FT-200/2sp (Std.)	FT-200/2sp (Opt.)
Tail stock	Type of tailstock	-	-	-
	Quill center taper	-	-	-
	Quill stroke	mm inch	-	-
	Tailstock body travel	mm inch	-	-
	Quill dia.	mm inch	-	-
	Tailstock Max. thrust	kgf lbs	-	-
	Type of center	-	-	-
	Tailstock traverse	mm/min ipm	-	-
	Tailstock body driven method	mm	-	-
	Tailstock clamping force	kgf lbs	-	-
Motors	Spindle motor	Model(Maker)	-	1FE1114-6WT11-1BZ2(Siemens)
		Power (30min/cont.)	kW HP	15/11.7 (20/15.6)
	X Axis	Model(Maker)	-	1FT6081-8AF71-1AG1(Siemens)
		Power	kW HP	2.1 (2.8HP)
		Torque(Rated)	kgf.cm ft.lbs	67.3(6.6 N.m) (4.87)
	Z Axis	Model(Maker)	-	1FT6081-8AF71-1AG1(Siemens)
		Power	kW HP	2.1 (2.8HP)
		Torque(Rated)	kgf.cm ft.lbs	67.3(6.6 N.m) (4.87)
	Turret	Model(Maker)	-	HC-SF121(Mitsubishi)
		Power	kW HP	1.2 (1.6HP)
		Torque(Max. /Rated)	kgf.m ft.lbs	3.4(34.4N.m) (24.4)
	Rotary tool	Model(Maker)	-	-
		Power	kW HP	-
		Torque(Rated)	kgf.m ft.lbs	-
	Hydraulic		kW HP	2.2 (3.0)
	Coolant		kW HP	0.4 (0.53)
	Lubricant motor		kW HP	0.053 (0.071)
Spindle Cooling		kW HP	0.4 (0.53)	